



## Safety Data Sheet

Copyright, 2015, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	11-3433-7	<b>Version Number:</b>	10.00
<b>Issue Date:</b>	04/16/15	<b>Supersedes Date:</b>	01/04/12

### Product identifier

3M(TM) Scotch-Weld(TM) Epoxy Adhesive 2216 B/A Translucent

### ID Number(s):

62-3508-0530-5, 62-3508-0535-4, 62-3508-5430-3, 62-3508-6430-2, 62-3508-7430-1

### Recommended use

Structural adhesive

### Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Industrial Adhesives and Tapes Division
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

### Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

**This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:**

10-3171-5, 10-3173-1

**DISCLAIMER:** The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at [www.3M.com](http://www.3M.com)



## Safety Data Sheet

Copyright, 2015, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	10-3171-5	<b>Version Number:</b>	24.00
<b>Issue Date:</b>	04/16/15	<b>Supersedes Date:</b>	01/04/12

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Adhesive 2216 Translucent Part B

#### Product Identification Numbers

62-3508-8535-6, 62-3508-9530-6

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Part B of Structural 2-Component Epoxy Adhesive, Structural adhesive

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Industrial Adhesives and Tapes Division
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

Skin Sensitizer: Category 1.

#### 2.2. Label elements

##### Signal word

Warning

##### Symbols

Exclamation mark |

##### Pictograms



**Hazard Statements**

Causes eye irritation.  
May cause an allergic skin reaction.

**Precautionary Statements**

**Prevention:**

Avoid breathing dust/fume/gas/mist/vapors/spray.  
Wear protective gloves.  
Wash thoroughly after handling.  
Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice/attention.  
IF ON SKIN: Wash with plenty of soap and water.  
If skin irritation or rash occurs: Get medical advice/attention.  
Wash contaminated clothing before reuse.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**2.3. Hazards not otherwise classified**

None.

**SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
Epoxy Resin	25068-38-6	100

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

#### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Aldehydes	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Ketones	During Combustion

#### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

#### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

For industrial or professional use only. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

## 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from oxidizing agents. Store away from areas where product may come into contact with food or pharmaceuticals.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

##### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

##### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>General Physical Form:</b>	Liquid
<b>Specific Physical Form:</b>	Viscous
<b>Odor, Color, Grade:</b>	transparent, epoxy odor.
<b>Odor threshold</b>	<i>No Data Available</i>
<b>pH</b>	<i>Not Applicable</i>
<b>Melting point</b>	<i>Not Applicable</i>
<b>Boiling Point</b>	<i>Not Applicable</i>
<b>Flash Point</b>	248 °C [ <i>Test Method: Pensky-Martens Closed Cup</i> ]
<b>Evaporation rate</b>	<i>Not Applicable</i>

Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>
Vapor Pressure	<=0.03 mmHg [@ 77 °C]
Vapor Density	<i>Not Applicable</i>
Density	1.17 g/ml
Specific Gravity	1.17 [Ref Std: WATER=1]
Solubility in Water	Nil
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	Approximately 14,000 centipoise
Hazardous Air Pollutants	0 % weight [Test Method: Calculated]
VOC Less H2O & Exempt Solvents	3.9 g/l [Test Method: calculated SCAQMD rule 443.1] [Details: when used as intended with Part A]
VOC Less H2O & Exempt Solvents	0 g/l [Test Method: calculated SCAQMD rule 443.1] [Details: as supplied]
VOC Less H2O & Exempt Solvents	0.4 % [Test Method: calculated SCAQMD rule 443.1] [Details: when used as intended with Part A]

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

### 10.5. Incompatible materials

Strong acids

Strong oxidizing agents

### 10.6. Hazardous decomposition products

#### Substance

None known.

#### Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1. Information on Toxicological effects****Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

**Inhalation:**

This product may have a characteristic odor; however, no adverse health effects are anticipated.

**Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye Contact:**

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Epoxy Resin	Dermal	Rat	LD50 > 1,600 mg/kg
Epoxy Resin	Ingestion	Rat	LD50 > 1,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Epoxy Resin	Rabbit	Mild irritant

**Serious Eye Damage/Irritation**

Name	Species	Value
Epoxy Resin	Rabbit	Moderate irritant

**Skin Sensitization**

Name	Species	Value
Epoxy Resin	Human and animal	Sensitizing

**Respiratory Sensitization**

Name	Species	Value
Epoxy Resin	Human	Some positive data exist, but the data are not sufficient for classification

**Germ Cell Mutagenicity**

Name	Route	Value
Epoxy Resin	In vivo	Not mutagenic
Epoxy Resin	In Vitro	Some positive data exist, but the data are not sufficient for classification



**Carcinogenicity**

Name	Route	Species	Value
Epoxy Resin	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Epoxy Resin	Ingestion	Not toxic to female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Epoxy Resin	Ingestion	Not toxic to male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Epoxy Resin	Dermal	Not toxic to development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
Epoxy Resin	Ingestion	Not toxic to development	Rat	NOAEL 750 mg/kg/day	2 generation

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Epoxy Resin	Dermal	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,000 mg/kg/day	2 years
Epoxy Resin	Dermal	nervous system	All data are negative	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Epoxy Resin	Ingestion	auditory system   heart   endocrine system   hematopoietic system   liver   eyes   kidney and/or bladder	All data are negative	Rat	NOAEL 1,000 mg/kg/day	28 days

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information****Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

## SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

### 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: Other information

### NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 1 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document Group:</b>	10-3171-5	<b>Version Number:</b>	24.00
<b>Issue Date:</b>	04/16/15	<b>Supersedes Date:</b>	01/04/12

**DISCLAIMER:** The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**



## Safety Data Sheet

Copyright, 2015, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	10-3173-1	<b>Version Number:</b>	25.00
<b>Issue Date:</b>	04/16/15	<b>Supersedes Date:</b>	01/04/12

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Adhesive 2216 Translucent Part A

#### Product Identification Numbers

62-3608-8535-4, 62-3608-9530-4

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Part a of two part epoxy adhesive, Structural adhesive

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Industrial Adhesives and Tapes Division
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Acute Toxicity (dermal): Category 4.  
Serious Eye Damage/Irritation: Category 1.  
Skin Corrosion/Irritation: Category 2.  
Skin Sensitizer: Category 1.  
Reproductive Toxicity: Category 1B.

#### 2.2. Label elements

##### Signal word

Danger

##### Symbols

Corrosion | Exclamation mark | Health Hazard |

##### Pictograms



**Hazard Statements**

Harmful in contact with skin.  
 Causes serious eye damage.  
 Causes skin irritation.  
 May cause an allergic skin reaction.  
 May damage fertility or the unborn child.

**Precautionary Statements**

**Prevention:**

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Avoid breathing dust/fume/gas/mist/vapors/spray.  
 Wear eye/face protection.  
 Wear protective gloves.  
 Wash thoroughly after handling.  
 Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 IF ON SKIN: Wash with plenty of soap and water.  
 Immediately call a POISON CENTER or doctor/physician.  
 If skin irritation or rash occurs: Get medical advice/attention.  
 Take off contaminated clothing and wash it before reuse.  
 IF exposed or concerned: Get medical advice/attention.

**Storage:**

Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**2.3. Hazards not otherwise classified**

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

90% of the mixture consists of ingredients of unknown acute oral toxicity.  
 90% of the mixture consists of ingredients of unknown acute dermal toxicity.

**SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
ALIPHATIC POLYMER DIAMINE	68911-25-1	80 - 90 Trade Secret *
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	4246-51-9	10 - 20 Trade Secret *
TOLUENE	108-88-3	< 1 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### **Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### **Eye Contact:**

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### **If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

#### Substance

Amine Compounds  
Carbon monoxide  
Carbon dioxide  
Oxides of Nitrogen

#### Condition

During Combustion  
During Combustion  
During Combustion  
During Combustion

### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or

bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

For industrial or professional use only. Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from oxidizing agents.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
TOLUENE	108-88-3	OSHA	TWA:200 ppm;CEIL:300 ppm	
TOLUENE	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin
TOLUENE	108-88-3	CMRG	STEL:75 ppm	Skin Notation

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

<b>General Physical Form:</b>	Liquid
<b>Specific Physical Form:</b>	Viscous
<b>Odor, Color, Grade:</b>	amber, pungent odor.
<b>Odor threshold</b>	<i>No Data Available</i>
<b>pH</b>	<i>Not Applicable</i>
<b>Melting point</b>	<i>Not Applicable</i>
<b>Boiling Point</b>	<i>Not Applicable</i>
<b>Flash Point</b>	>=94 °C [ <i>Test Method: Estimated</i> ]
<b>Evaporation rate</b>	<i>Not Applicable</i>
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Flammable Limits(LEL)</b>	<i>No Data Available</i>
<b>Flammable Limits(UEL)</b>	<i>No Data Available</i>
<b>Vapor Pressure</b>	<=0.01 mmHg [ <i>@ 20 °C</i> ]
<b>Vapor Density</b>	<i>Not Applicable</i>
<b>Density</b>	0.97 g/ml
<b>Specific Gravity</b>	0.970 [ <i>Ref Std: WATER=1</i> ]
<b>Solubility in Water</b>	Nil
<b>Solubility- non-water</b>	<i>No Data Available</i>
<b>Partition coefficient: n-octanol/ water</b>	<i>No Data Available</i>
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Decomposition temperature</b>	<i>No Data Available</i>
<b>Viscosity</b>	Approximately 7,000 centipoise [ <i>@ 20 °C</i> ]
<b>Hazardous Air Pollutants</b>	< 0.3 % weight [ <i>Test Method: Calculated</i> ]
<b>VOC Less H2O &amp; Exempt Solvents</b>	3.9 g/l [ <i>Test Method: calculated SCAQMD rule 443.1</i> ] [ <i>Details: when used as intended with Part B</i> ]
<b>VOC Less H2O &amp; Exempt Solvents</b>	< 10 g/l [ <i>Test Method: calculated SCAQMD rule 443.1</i> ] [ <i>Details: as supplied</i> ]
<b>VOC Less H2O &amp; Exempt Solvents</b>	0.4 % [ <i>Test Method: calculated SCAQMD rule 443.1</i> ] [ <i>Details: when used as intended with Part B</i> ]

**SECTION 10: Stability and reactivity****10.1. Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.



## 10.2. Chemical stability

Stable.

## 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

## 10.4. Conditions to avoid

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

## 10.5. Incompatible materials

Strong oxidizing agents

## 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

#### Skin Contact:

Harmful in contact with skin. Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

#### Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

#### Additional Health Effects:

#### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

#### Additional Information:

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE 1,000 - 2,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000 mg/kg
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	Dermal	Rabbit	LD50 2,500 mg/kg
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	Ingestion	Rat	LD50 3,160 mg/kg
TOLUENE	Dermal	Rat	LD50 12,000 mg/kg
TOLUENE	Inhalation-Vapor (4 hours)	Rat	LC50 30 mg/l
TOLUENE	Ingestion	Rat	LD50 5,550 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
Overall product		Irritant
ALIPHATIC POLYMER DIAMINE	Rabbit	Irritant
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	Rabbit	Corrosive
TOLUENE	Rabbit	Irritant

#### Serious Eye Damage/Irritation

Name	Species	Value
ALIPHATIC POLYMER DIAMINE	similar health hazards	Corrosive
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	similar health hazards	Corrosive
TOLUENE	Rabbit	Moderate irritant

#### Skin Sensitization

Name	Species	Value
Overall product		Sensitizing
ALIPHATIC POLYMER DIAMINE	Guinea pig	Sensitizing
TOLUENE	Guinea pig	Not sensitizing

#### Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

#### Germ Cell Mutagenicity

Name	Route	Value
------	-------	-------

TOLUENE	In Vitro	Not mutagenic
TOLUENE	In vivo	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
TOLUENE	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
TOLUENE	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
TOLUENE	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
TOLUENE	Inhalation	Some positive female reproductive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
TOLUENE	Inhalation	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 2.3 mg/l	1 generation
TOLUENE	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
TOLUENE	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
TOLUENE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
TOLUENE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
TOLUENE	Inhalation	immune system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 0.004 mg/l	3 hours
TOLUENE	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
TOLUENE	Inhalation	auditory system   nervous system   eyes   olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
TOLUENE	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
TOLUENE	Inhalation	heart   liver   kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 11.3 mg/l	15 weeks
TOLUENE	Inhalation	endocrine system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	4 weeks
TOLUENE	Inhalation	immune system	Some positive data exist, but the	Mouse	NOAEL Not	20 days

			data are not sufficient for classification		available	
TOLUENE	Inhalation	bone, teeth, nails, and/or hair	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 1.1 mg/l	8 weeks
TOLUENE	Inhalation	hematopoietic system   vascular system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
TOLUENE	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
TOLUENE	Ingestion	heart	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 2,500 mg/kg/day	13 weeks
TOLUENE	Ingestion	liver   kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
TOLUENE	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 600 mg/kg/day	14 days
TOLUENE	Ingestion	endocrine system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 105 mg/kg/day	28 days
TOLUENE	Ingestion	immune system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 105 mg/kg/day	4 weeks

**Aspiration Hazard**

Name	Value
TOLUENE	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations**

**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**EPA Hazardous Waste Number (RCRA):** Not regulated

## SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

### 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: Other information

### NFPA Hazard Classification

Health: 3 Flammability: 1 Instability: 1 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document Group:</b>	10-3173-1	<b>Version Number:</b>	25.00
<b>Issue Date:</b>	04/16/15	<b>Supersedes Date:</b>	01/04/12

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness

or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**