PLEASE NOTE: The membrane is held in position by an O-ring (6 mm diam). The CHM4's three 2 mm pins are intended to position and hold the chamber and are not intended for holding the membrane. To achieve a tight seal around the membrane, a thin film of vacuum grease applied to the O-ring is recommended. If you have any questions or suggestions, please contact:

World Precision Instruments

175 Sarasota Blvd, Sarasota, FL 34240 Tel: 941-371-1003 • Fax: 941-377-5428 E-mail: wpi@wpiinc.com



PLEASE NOTE: The membrane is held in position by an O-ring (6 mm diam). The CHM4's three 2 mm pins are intended to position and hold the chamber and are not intended for holding the membrane. To achieve a tight seal around the membrane, a thin film of vacuum grease applied to the O-ring is recommended. If you have any questions or suggestions, please contact:

World Precision Instruments

175 Sarasota Blvd, Sarasota, FL 34240 Tel: 941-371-1003 • Fax: 941-377-5428 E-mail: wpi@wpiinc.com



PLEASE NOTE: The membrane is held in position by an O-ring (6 mm diam). The CHM4's three 2 mm pins are intended to position and hold the chamber and are not intended for holding the membrane. To achieve a tight seal around the membrane, a thin film of vacuum grease applied to the O-ring is recommended. If you have any guestions or suggestions, please contact:

World Precision Instruments

175 Sarasota Blvd, Sarasota, FL 34240 Tel: 941-371-1003 • Fax: 941-377-5428 E-mail: wpi@wpiinc.com



PLEASE NOTE: The membrane is held in position by an O-ring (6 mm diam). The CHM4's three 2 mm pins are intended to position and hold the chamber and are not intended for holding the membrane. To achieve a tight seal around the membrane, a thin film of vacuum grease applied to the O-ring is recommended. If you have any questions or suggestions, please contact:

World Precision Instruments

175 Sarasota Blvd, Sarasota, FL 34240 Tel: 941-371-1003 • Fax: 941-377-5428 E-mail: wpi@wpiinc.com

